RZR Turbo R Ultimate Orange Madness



Key Specifications		
181	74"	16"
HP	WIDTH	CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	925cc
Drive System Type	Isolated Xtreme Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged
Fuel System/Battery	Electronic Fuel Injection
Horsepower	181 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Box Capacity300 lb (136 kg)Estimated Dry Weight2013 lb (913 kg)Fuel Capacity12 gal (45.4 L)Ground Clearance16 in (40.6 cm)Hitch Towing RatingN/AOverall Vehicle Size (L x W x H)128 x 74 x 74.4 in (325 x 188 x 189 cm)Payload Capacity730 lb (331 kg)		
Estimated Dry Weight2013 lb (913 kg)Fuel Capacity12 gal (45.4 L)Ground Clearance16 in (40.6 cm)Hitch Towing RatingN/AOverall Vehicle Size (L x W x H)128 x 74 x 74.4 in (325 x 188 x 189 cm)Payload Capacity730 lb (331 kg)	Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)
Fuel Capacity12 gal (45.4 L)Ground Clearance16 in (40.6 cm)Hitch Towing RatingN/AOverall Vehicle Size (L x W x H)128 x 74 x 74.4 in (325 x 188 x 189 cm)Payload Capacity730 lb (331 kg)	Box Capacity	300 lb (136 kg)
Ground Clearance16 in (40.6 cm)Hitch Towing RatingN/AOverall Vehicle Size (L x W x H)128 x 74 x 74.4 in (325 x 188 x 189 cm)Payload Capacity730 lb (331 kg)	Estimated Dry Weight	2013 lb (913 kg)
Hitch Towing RatingN/AOverall Vehicle Size (L x W x H)128 x 74 x 74.4 in (325 x 188 x 189 cm)Payload Capacity730 lb (331 kg)	Fuel Capacity	12 gal (45.4 L)
Overall Vehicle Size (L x W x H) 128 x 74 x 74.4 in (325 x 188 x 189 cm) Payload Capacity 730 lb (331 kg)	Ground Clearance	16 in (40.6 cm)
Payload Capacity 730 lb (331 kg)	Hitch Towing Rating	N/A
	Overall Vehicle Size (L x W x H)	128 x 74 x 74.4 in (325 x 188 x 189 cm)
Wheelbase96 in (244 cm)	Payload Capacity	730 lb (331 kg)
	Wheelbase	96 in (244 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Cargo System	Lock & Ride®
Doors	Full Door
Electronic Power Steering	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with Integrated EPS Modes and Ride Command Push Button Controls
Hitch Type	Not Equipped
Instrumentation	RIDE COMMAND [™] 7" Glove-Touch Display: Built-In GPS, Mapping, Vehicle-to-Vehicle with *Group Ride, Follow the Leader, & Messaging. Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, and 2 Front Speakers, and External 400W Amp) Dual- sweep Analog Dials w/ 4 in LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator
Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting
Other Standard Features	RIDE COMMAND®, High Output 900W Charging System, Polaris Pulse System, In-Dash Charge Port, 2 front DC Accy ports, Polaris P.A.S.S., Painted Aluminum Roof, Colored Toe Link, Mud and Rock Guards
Seat Type	Color-Matched Bolstered Bucket Seats with Driver 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) & Passenger tilt adjustability; Retractable Click-6 Harnesses

TIRES / WHEELS

Front Tires	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
Rear Tires	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
Wheels	Painted Cast Aluminum Rim with 5-Lug Pattern

SUSPENSION

Dynamix DV with Selectable Ride Modes: Comfort, Rock, Track, Baja
FOX 3.0 Live Valve X2 Internal Bypass (Electronically Controlled Compression and Rebound)
Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 27.0″ (68.6 cm) Usable Travel, 22.25″ (56.5 cm) Wheel Travel, Unitized Hubs
FOX 3.0 Live Valve X2 Internal Bypass (Electronically Controlled Compression and Rebound)
Tubular Trailing Arm with boxed gusseting and Toe Link, High Clearance Radius Rods, and Stabilizer Bar and 28.3" (71.9cm) Usable Travel, 22.4" (56.9 cm) Wheel Travel, Unitized Hubs